

## Solution 2000 / 3000 Control Panel



The Solution 2000 and Solution 3000 are new generation alarm control panels for small residential & commercial markets.

### System overview

Supporting up to 8 fully programmable zones on the Solution 2000 and 16 fully programmable zones on the Solution 3000, this range of intrusion panels is suitable for any home, and even some commercial premises.

With support for up to four keypads on both panels and the ability to be split into two separate partitions on the Solution 3000, you have the flexibility of one security system that can act as two.

### Functions

#### User Interfaces

The Solution 2000 and 3000 control panels have the variety of keypad options, including LCD Icon, LCD Alphanumeric, and various touchscreen options that are simple to use.

#### Wireless

The Solution 2000 supports the WE800EV2 wireless receiver for wireless keyfob control, while the Solution 3000 supports both the WE800EV2 and the option to integrate with the Bosch RADION range of wireless transmitters.

#### Communication

Solution 2000 and 3000 also have available a range of communications extension modules that integrate directly with the panel and provide options such as mobile communications via GPRS networks, along with IP reporting through the internet.

- ▶ 8/16 Fully Programmable Zones
- ▶ 33 Codes - 1 Installers, 32 User Codes
- ▶ 16 Wireless Devices (on Solution 3000)
- ▶ Partitionable into 2 Separate Areas
- ▶ STAY / AWAY Arming Options

The IP module includes CSV-IP communications technology and makes the panels fully NBN-ready / Fiber compatible with the majority of monitoring centers in Australia, New Zealand and Asia Pacific who can handle the IP communications from the Solution 2000 and 3000.

#### Remote Security Control Plus (RSC+) app

Remote Security Control Plus (RSC+) app allows users to control their security systems remotely from mobile devices such as phones and tablets. You can arm / disarm the control panel and control connected devices such as lighting and A/C, and select the events you want to receive push notifications.

### Regulatory information

Australia	RCM AS/CA S002:2010
New Zealand	Telepermit
Europe	PCE - EN61000-3:2007/A1:2011 EN50130-4:2011

### Technical specifications

#### Power Requirements

Primary	TF008 Plug Pack (only sold in Australia)
Secondary	12 VDC, 6.5Ah from rechargeable sealed lead/acid battery

## Communications

Communications	CID, SIA, Email*, Domestic Dialing, CSV-IP, Push Notification* *Requires B426-M IP Communications Module or B450-M Universal Communications Module
----------------	-------------------------------------------------------------------------------------------------------------------------------------------------------

## Environmental Considerations

Temperature	0° to +45°C
Relative Humidity	10% to 95% non-condensing

## Enclosure

Dimensions (H x W x D) (packed in carton)	306 x 262 x 84mm
Weight	2.5kg
Warranty	3 years

## Ordering information

### ICP-SOL2-P Control panel PCBA, 8-zone

Sold in Australia, New Zealand and APR region  
Order number **ICP-SOL2-P | F.01U.292.968**

### ICP-SOL3-P Control panel, 16-zone

Sold in Australia, New Zealand and APR region  
Order number **ICP-SOL3-P | F.01U.292.967**

### ICP-SOL2-APR Control panel, 8-zone, 230VAC

Only sold in APR region  
Order number **ICP-SOL2-APR | F.01U.310.793**

### ICP-SOL3-APR Control panel, 16-zone, 230VAC

Only sold in APR region  
Order number **ICP-SOL3-APR | F.01U.310.794**

## Accessories

### IUI-SOL-TS5 TouchOne Mini 5"

Only sold in Australia  
Order number **IUI-SOL-TS5 | F.01U.335.887**

### IUI-SOL-TS7 TOUCHONE 7" CODE PAD SDI2

Only sold in Australia  
Order number **IUI-SOL-TS7 | F.01U.303.249**

### IUI-SOL-TEXT LCD alphanumeric keypad

LCD text keypad, two lines with each 18 characters  
Order number **IUI-SOL-TEXT | F.01U.301.795**

### IUI-SOL-ICON LCD icon keypad, 16-zone

Shows 8 zones, provides LCD, and provides a protective door  
Order number **IUI-SOL-ICON | F.01U.301.794**

### B308 SDI2 8-Output Expansion Module

Provides 8 programmable relays.  
Order number **B308 | F.01U.323.802 F.01U.397.025 F.01U.385.672**

### B426-M Ethernet communication module, mobile

Supports Ethernet communication for remote programming and mobile apps on AMAX and Solution Series control panels  
Order number **B426-M | F.01U.332.307 F.01U.386.953**

### B450-M Plug-in communicator interface, mobile

Supports cellular communication for remote programming and mobile apps on AMAX and Solution Series control panels  
Order number **B450-M | F.01U.332.308 F.01U.387.027**

### B443 Plug-in Cellular, HSPA+ (3G+)

Multi-function 3G/4G cellular communicator providing IP communication over a GPRS/EDGE/UMTS/HSPA+ cellular network  
Order number **B443 | F.01U.323.796 F.01U.385.515**

## Services

### EWE-CTRCOM-IW 12 mths wrty ext Control Communicator

12 months warranty extension  
Order number **EWE-CTRCOM-IW | F.01U.352.289**

#### Represented by:

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
www.boschsecurity.com/xc/en/contact/  
www.boschsecurity.com

**Germany:**  
Bosch Sicherheitssysteme GmbH  
Robert-Bosch-Ring 5  
85630 Grasbrunn  
Tel.: +49 (0)89 6290 0  
Fax: +49 (0)89 6290 1020  
de.securitysystems@bosch.com  
www.boschsecurity.com

**North America:**  
Bosch Security Systems, LLC  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
onlinehelp@us.bosch.com  
www.boschsecurity.com

**Asia-Pacific:**  
Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
www.boschsecurity.com/xc/en/contact/  
www.boschsecurity.com